

HEGA WALL PUTTY-GRAY 200

TECHNICAL DETAILS

01) Hega Wall Putty- Gray 200 is a high-quality cement-based powder that provides an ideal filling and leveling material for all-purpose cement sand-plastered walls, concrete ceilings, concrete walls, and pre-cast walls.

02) Hega Wall Putty -Gray 200 provides resistance to water in the humid air.

03) Highly recommended for interior/exterior and exposed surfaces.

04) Hega Wall Putty-Gary 200 powder to be mixed with water as advised for direct application to fill and level the required surfaces as desired.

05) Not recommended for use on painted or other non-cementations surfaces.

06) **Mixing Ratio-**

Will depend on the application. If the application needs more filling and leveling, the paste should be prepared with less water to get a thicker paste so that the paste can be applied to fill the void on the surface with easy.

07) **Application Method-**

Option One if the surface is generally even

1st coat 2.5mm and after 24 hours apply the 2nd coat with 1.5mm

Option two if the surface is a un even-maximum thickness of 7mm

1st coat 4mm and after 24 hours of curing apply 2nd coat of 3mm

(24 hours of curing should be allowed after each and every coat application)

After the surface completion of the above process apply Hega Wall Putty –White 1st coat leave 24 hours and apply 2nd coat.

Allowed complete drying for further one day and cut and remove excess material application marks with the use of white sandpaper 120 and then use of water sandpaper 150 to obtain a very smooth surface which is an ideal base for paintwork.

STORAGE

- 01) Store Hega Wall Putty-Gary 200 in a dry place. Open the just before use.
- 02) Pot life 3 hrs

REMARK Structural problems could not be taken care of by the finishing/ decoration Material. Therefore, adequate assurance of structure is strongly recommended. We are Available for technical experience sharing at any stage of the project.

Safety: Please make sure to use proper safety equipments such as dust masks/eye protectors, Hand gloves ext. When using this product.

Manufactured By Horana Minerals (Pvt) Ltd.