

## **HEGA TILE MORTAR**

Hega Tile Mortar is a regular-setting, polymer-enriched (“modified”) mortar for Fixing ceramic and porcelain tiles, granite, marble for both internal and external floor and wall in thin-set applications.

Hega Tile mortar is both hydraulically and organically bound which ensure good adhesion of the tile to the surface. For use on all cement-bound substrates with dimensionally stable plastered substrates.

### **Advantage**

Ultimate performance over many substrates.

Excellent workability with optimum thin and medium bed performance.

Excellent adhesion to different substrate.

Economical, High stability, Water resistant

### **Recommended Applications**

- A) Concrete, Cement renders
- B) Mortar Beds
- C) Cement Plasters
- d) Concrete or brick masonry

## **New Way Of Fixing Wall and Floor Tiles** **Easy/Durable/Economical and long lasting**

1. Clean the surface thoroughly and it must be free from dust, grease, wax, oil, dirt and other contaminants and wet the surface.

2. Add approx 6-8 liters of clean water to a bucket and mix the 25kg of Hega Tile mortar thoroughly.

3. Spread the tile mortar to the surface by using proper trowel.  
Use 6mm \* 9mm trowel for larger size tiles and 6mm \* 6mm trowel for smaller  
Size tiles
- 4 Lay the tiles with a good pressure, twisting to ensure good contact with the mortar  
and adjust the tile level with the help of rubber hammer.
5. Remove the excess mortar immediately after the application before drying using a  
Damp cloth.
6. Cure for a minimum 24 hours .Prevent trafficking before tiles firmly fixed.

#### Recommended Applications

- D) Concrete, Cement renders
- E) Mortar Beds
- F) Cement Plasters
- D) Concrete or brick masonry

***Manufactured by Horana Minerals (Pvt) Ltd***